



Item #	Bore Diameter (d)	Outer Diameter (D)	Width (B)	Min. Radius (rs)	Load Rating (Cr)	Max. Speed (Grease) x 1000	Max. Speed (Oil) x 1000	Closure
ET2015	15 mm 0.5906 in	20 mm 0.8268 in	3.5 mm 0.1378 in	0.15 mm 0.0059 in	942 N	22 rpm	26 rpm	-
ET2115	15 mm 0.5906 in	21 mm 0.8268 in	3.5 mm 0.1378 in	0.15 mm 0.0059 in	939 N	22 rpm	26 rpm	-
ET2216	16 mm 0.6299 in	22 mm 0.8661 in	4.0 mm 0.1575 in	0.15 mm 0.0059 in	968 N	20 rpm	24 rpm	-
ET2316	16 mm 0.6299 in	23 mm 0.9055 in	4.5 mm 0.1772 in	0.15 mm 0.0059 in	968 N	20 rpm	24 rpm	-
ET2418	18 mm b0.7087 in	24 mm 0.9445 in	4.0 mm 0.1575 in	0.15 mm 0.0059 in	988 N	18 rpm	21 rpm	-
ET2520	20 mm 0.7874 in	25 mm 0.9843 in	4.0 mm 0.1575 in	0.15 mm 0.0059 in	1011 N	17 rpm	20 rpm	-
ET2316ZZ	16 mm 0.6299 in	4.5 mm 0.1772 in	4.5 mm 0.1772 in	-	968 N	20 rpm	24 rpm	Steel shield with snap ring
ET2520ZZ	20 mm 0.7874 in	4.0 mm 0.1575 in	4.0 mm 0.1575 in	-	1011 N	17 rpm	20 rpm	Steel shield with snap ring
ER1038	9.525 mm	15.875 mm	3.967 mm	0.25 mm	856 N	30 rpm	35 rpm	-
ER1038	0.3750 in	0.6250 in	0.1562 in	0.0098 in	856 N	30 rpm	35 rpm	-
ER1212	12.700 mm	19.050 mm	3.967 mm	0.25 mm	918 N	24 rpm	28 rpm	-
ER1212	0.5000 in	0.7500 in	0.1562 in	0.0098 in	918 N	24 rpm	28 rpm	-
ER1458	15.875 mm	22.525 mm	3.967 mm	0.25 mm	968 N	20 rpm	24 rpm	-
ER1458	0.6250 in	0.8750 in	0.1562 in	0.0098 in	968 N	20 rpm	24 rpm	-

ER1634	19.050 mm	25.400 mm	3.967 mm	0.25 mm	1011 N	17 rpm	20 rpm	-
ER1634	0.7500 in	1.0000 in	0.1562 in	0.0098 in	1011 N	17 rpm	20 rpm	-
ER1038ZZ	9.525 mm	3.967 mm	3.967 mm	-	856 N	30 rpm	35 rpm	Steel shield with snap ring
ER1038ZZ	0.3750 in	0.1562 in	0.1562 in	-	856 N	30 rpm	35 rpm	Steel shield with snap ring
ER1212ZZ	12.700 mm	3.967 mm	3.967 mm	-	918 N	24 rpm	28 rpm	Steel shield with snap ring
ER1212ZZ	0.5000 in	0.1562 in	0.1562 in	-	918 N	24 rpm	28 rpm	Steel shield with snap ring
ER1458ZZ	15.875 mm	3.967 mm	3.967 mm	-	968 N	20 rpm	24 rpm	Steel shield with snap ring
ER1458ZZ	0.6250 in	0.1562 in	0.1562 in	-	968 N	20 rpm	24 rpm	Steel shield with snap ring
ER1634ZZ	19.050 mm	3.967 mm	3.967 mm	-	1011 N	17 rpm	20 rpm	Steel shield with snap ring
ER1634ZZ	0.7500 in	0.1562 in	0.1562 in	-	1011 N	17 rpm	20 rpm	Steel shield with snap ring

ET2316ZZ	16 mm 0.6299 in	4.5 mm 0.1772 in	4.5 mm 0.1772 in		968 N	20 rpm	24 rpm
ET2520ZZ	20 mm	4.0 mm	4.0 mm		1011 N	17 rpm	20 rpm
	0.7874 in	0.1575 in	0.1575 in				
Item #	Bore Diameter (d)	Width(B)	Width (B1)		Load Rating (Cr)	Max. Speed (Cr) x 1000	Max. Speed (Oil) x 1000
ER1038ZZ	9.525 mm	3.967 mm	3.967 mm		856 N	30 rpm	35 rpm
	0.3750 in	0.1562 in	0.1562 in				
ER1212ZZ	12.700 mm	3.967 mm	3.967 mm		918 N	24 rpm	28 rpm
	0.5000 in	0.1562 in	0.1562 in				
ER1458ZZ	15.875 mm	3.967 mm	3.967 mm		968 N	20 rpm	24 rpm
	0.6250 in	0.1562 in	0.1562 in				
ER1634ZZ	19.050 mm	3.967 mm	3.967 mm		1011 N	17 rpm	20 rpm
	0.7500 in	0.1562 in	0.1562 in				

Steel shield with snap ring

Steel shield with snap ring

Closure

Steel shield with snap ring

Steel shield with snap ring

Steel shield with snap ring

Steel shield with snap ring